## **Snow Mauler PV-400**

			TO BE SEED OF THE SECOND OF TH
Electrical	12 volts	Brakes	Air brakes
System			"S" cam type
	CLUMP 20 OCT L. (45 OOO II.)	<b>国际的国际区域的</b>	
Weight &	GVWR: 20,865 kg (46,000 lbs)	Hydraulic	Closed centre variable
Dimensions	Vehicle Weight: 11,340 kg (25,000 lbs)	System	displacement piston pump
	Wheelbase 378 cm (149 in)		
	Overall Length: 615 cm (242 in)	Cab	Series 90 Soundguard
	Overall width: 259 cm (102 in)		Cab is forward mount for
	Overall height: 330 cm (130 in)		excellent visibility
Comica	Autolita		Driver air seat with passenger
Carrier Specifications	4 wheel drive		jump seat for vehicle training
Specifications	Maximum working speed		
	90 kph / 56 mph	Engine Enclosure	Detachable for
Carrier Engine	Committee OSMA 444 400 UID	Enclosure	easy maintenance
(Electronic)	Cummins QSM - 11 400 HP	Frame	
(Discontinuo de la continuo de la co	1400 ft. lbs. torque	rrame	Heavy duty steel
	Charge air cooled		- 12" X 3-1/2" X 3/8"
Transmission	75 6		110,000 lb. tensile strength
manomiosion	ZF 6 speed automatic transmission	Paint Finish	DuraCoat industrial
	with integral transfer case	r ame r misn	powder coat finish
	Ratio: high 0.625 : 1		Your choice of colour
	low 5.35 : 1		Tour choice of colour
_ Radiator /	Remote mounted 20 hp hydraulic	Tires & Rims	All steel radials
Transmission	fan drive, thermostatically		425/65R 22.5
Oil Cooler	controlled / variable speed		20 Ply rated
Front Steer Axle	Arvin Meritor (Rockwell)	Fuel System	Capacity: 283 litres
	Capacity: 10,886 kg (23,000lbs)		(75 US gallons)
	Ratio: 7.17 : 1		
Rear Axle	Arvin Meritor (Rockwell)	Drive Line	Borg Warner mechanic
	Capacity: 10,886 kg (23,000 lbs)		8.5C yokes
	Ratio: 7.17 : 1		4" heavy wall tube

"Airport Technologies Inc. reserves the right to change specifications without prior notice."



P.O. Box 132

Southport Aerospace Centre Southport, Manitoba, Canada R0H 1N0

Telephone: (204) 428-5588 • Fax: (204) 428-5599

www.atifirst.com sales@atifirst.com